Ξ			0	₩ 2	•	
Z ØS Presultion						
			LAYOUT SHOWN AS EXA	MPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension	1				
Standard : Based on MIL-DTL-38999 Series III	Dim Nominal	-				
-Shell Material : Aluminium	ØS 32.5 Max Z 31 Max	-	SOURIAU shall not be liable for any r			
-Shell Plating : Nickel	VV THREAD M22x1-6g]	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party			
-Insulator : Thermoplastic -Contacts : Copper Alloy			(professional recommendatio			
-Seals & Grommet : Silicon Elastomer]	
-Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed		
-Durability : 500 Mating cycles						
-Delivered with Souriau contacts and Accessories			PN: 8D515F0	J5PN		
-Temperature Range <u>-</u> -65°C to +200°C			First Delegas			
-Salt Spray : 48 hours		A 19-10-2016				
-Mass : 26.04 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE				
BASIC SERIES: 8D 5 - 15 F 0	05 P N	SCALE	General linear Tolerances:	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding		NA		859		
CONTACT TYPE : Standard Crimp Contact	ORIE			This document is the p SOURIAU		
SHELL SIZE : 15 CONTACT TYPE : PIN(500 Matings)			WWW.SOURIAU.CC	JIVI it must not be repro- communicated without		
PLATING : F = Nickel	CONTACT LAY		SOURIAU E		SHEET	
		A3	8D515F05		1/2	

	工	G	г	m	D	0	
4		Contact Layout x e					
		X-axis (mm) Y-axis (mm) +.000 (0.00) +.100 (2.54) +.174 (4.42) +.024 (0.61) +.094 (2.39) 148 (3.76) 094 (2.39) 148 (3.76) 174 (4.42) +.024 (0.61)					
ω							
						SOURIAU shall not be liable due to a use of the Prod the Specifications issued by e (professional recom	lucts wl either o menda
N							Count FR
						PN: 8D	515
					A 19-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:	
					TITLE		lumir
<u> </u>					SCALE	General Tolerar ±	nces:
					SOURIA	OURIAU WWW.SOURIAU	
					FORMAT A3	SOUF 8D5	
	Н	G	F	E	D	C	
							-

