Part #: Mallory Sonalert Products, Inc. JT120-YG-CSL Revision: **Sales Outline Drawing** В **Specifications:** Stack Number: LED Color: YELLOW GREEN Connection Wires: Green and Brown Yellow and Brown LED Current Draw: <230mA <190mA 120 VAC Rated Voltage: Operating Voltage: 90-120 VAC Sound Level Category: Loud Loud Loud Loud Continuous for 5 sec then 0.1s Medium Pulse (5PPS) Double Pulse (0.5PPS) Mode of Operation: Continuous beep until reset Black and Gray Wires: Black and Gray Wires: Black and Gray wires; Orange and Black and Grav Connection: Orange wire connected Purple wire connected to Purple wires connected to Wires to Green/Yellow wire Green/Yellow wire Green/Yellow wire Sound Current Draw: 40mA Max. 80-85 dB(A) Typ. Loudness @ 1m: Frequency: 2000 ± 500 Hz **Total Max Current:** <460mA with all LED's and Sound unit working **Operating Temperature:** -25° ~ +60°C Opaque White Lens Color: ABS FR15U Material: Mounting Method: Stainless Steel Pole Weight Typical (g): 685 NEMA 12: Approved Please contact factory. Options: **cUL** Recognized **ROHS Compliant Dimensions:** Inches (mm) -5.2 [132.0] YELLOW GASKET GREEN -18.1 [459.8]-Ø0.57 [Ø14.6] Ø0.20 [Ø5.2] mounting 2.4 [61.8] 2.04 [51.9] --0.39 [9.9] 0.95 [24.3] 0.95 [24.3] 2.7 [68.31-MUUNTING TOP VIEW DIAGRAM SOUND OPERATION: CONNECT GRAY AND BLACK WIRES TO POWER FOR CONTINUOUS SOUND. FOR MEDIUM PULSE, CONNECT GRAY & BLACK TO POWER AND ORANGE WIRE TO GREEN/YELLOW WIRE. FOR DOUBLE PULSE, CONNECT GRAY & BLACK TO POWER AND PURPLE WIRE TO GREEN/YELLOW WIRE. FOR CONT/BEEP, CONNECT GRAY & BLACK TO POWER AND ORANGE & PURPLE TO