тніз	COPY IS F	PROVID	ED ON	A RESTRICTED BASIS AND IS NOT TO BE USE	D IN ANY WAY DETRIMENTAL T	O THE INT	ERESTS OF PANDUIT CORP.		
Mo	Material			High Conductivity Seamless Copper Tube					
	iting				(1) 1/0 str w/ (1) #1	str (1)) 2/0 str w/ (2) #4 str	(2) 1/0 str w/ (2)) #10 str
	iing			Electro-Tin	(3) #2 str	(1)) 3/0 str w/ (3) #8 str	(3) #2 str w/ (2)	#8 str
-					(1) 2/0 str w/ (1) #2	str (2) 1/0 str w/ (1) #12 str	(2) 1/0 str w/ (1)) #6 str
Wi	Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	(3) #2 str w/ (1) #12	str (3) #2 str w/ (3) #12 str	(1) 1/0 str w/ (2)) #2 str
					(5) #4 str	(3)) #2 str w/ (2) #10 str	(2) 1/0 str w/ (3)) #10 str
					(2) #1 str w/ (1) #4 s	str (1)) 3/0 str w/ (2) #6 str	(2) 1/0 str w/ (2)) #8 str
Wi	Wire Strip Length			1-1/16 in.	(3) #2 str w/ (1) #10	str (2)1/0 str w/ (1) #10 str	(1) 3/0 str w/ (3) #6 str
					(1) 3/0 str w/ (1) #4) 1/0 str w/ (2) #12 str	(3) #2 str w/ (3)	#8 str
UL	UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions	(2) 1/0 str) #2 str w/ (1) #6 str	(1) 3/0 str w/ (2	
C					(3) #2 str w/ (2) #12) 1/0 str w/ (1) #8 str	(2) 1/0 str w/ (1	
					(3) #2 str w/ (1) #8 s) #2 str w/ (3) #10 str	(2) 1/0 str w/ (2)	
				with applications greater than 2000 volts.	(2) #2 str w/ (2) #4 s) 1/0 str w/ (3) #12 str		
					(1) #1 str w/ (2) #2 s) 1/0 str w/ (3) #4 str		
	UL Temperature Rating			90°C			, no ou w (o) n ou		
	C.S.A Certified Wire Connector			Yes				N	
	Panduit Color Code on Barrel		ode	YELLOW				Z	
	Panduit Die Index No. on Barrel		x No.	P62				A	S ≥
	R	6	2					Color coded barrel markings–	
CERTIFIED LISTED Wire Connector									
									NLEY PARK, ILLINOIS
						PSCYEL-Q			
01				REVISED BARREL MARKING		PC00728			
REV	DATE	BY	CHK	DESCRIPTION	1	ECN	N/A	URAWING NU/ CAU FILE	