

W2S130 Series

Tubeaxial

150Øx55mm



- AC fans with external rotor shaded-pole motor. Impedance protected against overloading.
- Die-cast aluminum housing. Impeller of sheet-steel, directly welded onto rotor.
- Rotational direction CCW looking at rotor.
- Mounting from either face using two 4.5 mm holes.
- Electrical connection via 2 spade terminals.
- Cable length 330 mm.
- Mounting from either face using 2 4.3 mm (.169") holes.
- UL, CSA, VDE approvals on some models, please contact application engineering.

| Part Number | Curve | CFM @ 0 | VAC | Hertz | Power (W) | dBA | Max Amb. Temp C | Bearing Type | Features | Wgt. (lbs) |
|----------------|-------|---------|---------|-------|-----------|-----|-----------------|--------------|-----------|------------|
| W2S130-AA25-01 | 1 | 225 | 115 | 50/60 | 38 | 52 | 80 | Ball | Leads | 2.44 |
| W2S130-AA25-44 | 1 | 225 | 115 | 50/60 | 38 | 52 | 80 | Ball | Terminals | 2.44 |
| W2S130-AA25-51 | 1 | 225 | 115 | 50/60 | 38 | 52 | 80 | Ball | Terminals | 2.44 |
| W2S130-BM15-01 | 2 | 263 | 115 | 50/60 | 46 | 60 | 70 | Ball | Leads | 2.44 |
| W2S130-AA03-01 | 1 | 225 | 230 | 50/60 | 39 | 52 | 70 | Ball | Leads | 2.63 |
| W2S130-AA03-44 | 1 | 225 | 230 | 50/60 | 38 | 52 | 70 | Ball | Terminals | 2.63 |
| W2S130-AA03-51 | 1 | 225 | 230 | 50/60 | 38 | 52 | 70 | Ball | Terminals | 2.63 |
| W2S130-BM03-01 | 2 | 250 | 230 | 50/60 | 46 | 60 | 70 | Ball | Leads | 2.44 |
| W2S130-AA03-49 | 1 | 225 | 115/230 | 50/60 | 38 | 52 | 70 | Ball | Leads | 2.63 |

| Fan Type | Air Flow |
|-----------|---------------------|
| W2S130-AA | Exhaust over struts |
| W2S130-BM | Intake over struts |

