

Type 2 surge protection plug - VAL-MS 1000PV ST - 2805185

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Replacement plug for PV arrester combinations of the VAL-MS 1000 DC... product range



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	80.0 GRM
Custom tariff number	85363010
Country of origin	Germany

Technical data

Dimensions

Height	52.4 mm
Width	17.7 mm
Depth	54.5 mm
Horizontal pitch	1 Div.

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C

General

Housing material	PA 6.6
Inflammability class according to UL 94	V0
Color	black
Standards for air and creepage distances	IEC 60664-1
	IEC 61643-1
	EN 61643-11
Mounting type	On base element

Type 2 surge protection plug - VAL-MS 1000PV ST - 2805185

Technical data

General

Type	Male
Number of positions	1
Surge protection fault message	Optical
Direction of action	1L-N/PE

Protective circuit

IEC test classification	II
	T2
EN type	T2
Nominal voltage U_N	400 V AC
Maximum continuous operating voltage U_C	580 V AC
U_T (TOV-proof)	690 V AC (5 s)
Nominal frequency f_N	50 Hz (60 Hz)
Residual current I_{PE}	$\leq 250 \mu A$
Standby power consumption P_C	$\leq 0.15 VA$
Max. discharge current I_{max} (8/20) μs	30 kA
Nominal discharge current I_n (8/20) μs	15 kA
Impulse discharge current (10/350) μs , peak value I_{imp}	1.25 kA
Voltage protection level U_p	$\leq 2.5 kV$
Residual voltage	$\leq 2.5 kV$
	$\leq 2.3 kV$ (at 10 kA)
	$\leq 2.1 kV$ (at 5 kA)
	$\leq 1.9 kV$ (at 3 kA)
Response time	$\leq 25 ns$
Max. backup fuse with branch wiring	125 A (gL / gG)
Short-circuit resistance I_p with max. backup fuse (effective)	25 kA

Connection, protective circuit

Connection method	FLASHTRAB/VALVETRAB plug-in system connector
-------------------	----------------------------------------------

Standards and Regulations

Standards/regulations	IEC 61643-1 2005
	DIN EN 61643-11 2002

Classifications

eCl@ss

eCl@ss 4.0	27140201
------------	----------

Type 2 surge protection plug - VAL-MS 1000PV ST - 2805185

Classifications

eCl@ss

eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130805
eCl@ss 7.0	27130805
eCl@ss 8.0	27130805

ETIM

ETIM 2.0	EC000941
ETIM 3.0	EC000941
ETIM 4.0	EC000941
ETIM 5.0	EC000941

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

GOST / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals


Approvals submitted


Approval details


GOST

Type 2 surge protection plug - VAL-MS 1000PV ST - 2805185

Approvals

UL Recognized 

cUL Recognized 

cULus Recognized 

Drawings

Dimensioned drawing

