



В

А





RoHS

	2
	3-

		BULK	50 MICRO-INCHES [1.27um]		7-SP-3088R-K1-031					
	PACKAGE CONTACT PLATING IN MATING AREA			PART NUMBER						
	THIRD ANGL	E PROJECTION			11118 Susquehar	na Trail S	South			
	\bigcirc			(Q_[[[] 	Glen Rock, PA 17327–9199 (717) 235–7512 http://www.stewartconnector.com					
	DO NOT SO	CALE DRAWING	TTLE: EIGHT CONDUCTOR/EIGHT POSI		LINE CORD MOI	DUI F:				
_		s subject to Ithout notice	RADIAL BACK, KEY OPT			, ,				
	DIMENSIONS:	INCHES [METRIC]	THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONSENT OF STEWART CONNECTOR. ONE OR MORE U.S. PATENTS MAY APPLY TO THIS PRODUCT. FOR DETAILS, PLEASE VISIT: HTTP: //BELFUSE.COM/STEWART/STEWART_PATENTS/		drn by: KRL	DATE 1/	31/06			
	TOLERANCES	ERWISE SPECIFIED ARE ±.005 [0.13] S ARE ± 1°			APPD BY:	DATE 2-1-06				
	sheet no. 1	OF 1			DWG NO. CT3001	31 REV. B5				

2

2

1

DATE	REV	ECN	APP'D. BY
1/5/15	B4	10167	TRM
3–14–16	B5	10606	TRM
	1		

В

А

NOTES:

- 1- Plug Kit consists of : Pre-inserted plug housing
- 2- MATERIALS : FRONT HOUSING PLASTIC : POLYCARBONATE, UL 94-VO, COLOR: BLUE CONTACTS : PHOSPHOR BRONZE, SELECTIVE GOLD PLATING
- 3- CONTACTS TERMINATE STRANDED CONDUCTORS UP TO .031 [0.79] OUTSIDE DIAMETER OF INSULATION.
- 4- FOR PRODUCT SPECIFICATION SEE PR026-01.
- 5- DIMENSIONS AND TOLERANCES COMPLY WITH TIA-1096 STANDARD.
- ▲ TERMINATED PLUG HEIGHT: .237 [6.02] ±.005 [0.13]

1

AutoCAD

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bel: 937-SP-3088R-K1-031